H2O-FLOW

H2O
TORONTO

Our brand new 2022 edition to entry level commercial and residential applications, the H2O-FLOW is a full featured total solution unit intended for medium-low traffic solutions.

Featuring Tri-Temp dispensing, 4 Stage 50 GPD RO Filtration, and an in tank UV disinfection system, the H2O-FLOW is a modern designed quality unit with stainless steel internals, rugged structural design, and external brushed stainless steel panels; making the H2O-FLOW an ideal addition to any home, common area, kitchen, lobby or office.

Equipped with an extra-large dispensing gap, and simultaneously operable spigots for Cold, Ambient, and Hot Water, the H2O-FLOW is an ideal dispensing solution for water bottles and coffee pots.

SPECIFICATIONS & FEATURES

Dimensions	14" W x 14" L x 48" H
Weight	45 lbs
Cold Tank	1.2 gallon
Hot Tank	0.55 gallon
Cooling Rate	0.75 gal/hour 37-50°F
Heating Rate	1.0 gal/hour 180°F

55W 188 Btu/h Lock Rotor Compressor
Brushed Stainless Steel Panels
Hot, Ambient, & Cold Water
Hot Water Safety Lock

4-Stage Reverse Osmosis 50 GPD
Stage 1: Sediment (5 micron)
Stage 2: Pre-Carbon (1 micron)
Stage 3: Reverse Osmosis 50 GPD (0.01 micron)
Stage 4: Post Carbon Filter (0.5 micron)

Hot Power Consumption 700W
Cold Power Consumption 80W
110V~127V AC / 50-60Hz
Refrigerant R134A
Climate Class T

Sediment Filter
Removes particulate matter before reaching additional filters. Does not remove chemicals or heavy metals.

Pre-Carbon (GAC) Filter
Removes sediment and compounds that reduce second or third-stage filter life.

Reverse Osmosis Membrane
Reverse Osmosis systems remove pollutants from water including nitrates, pesticides, sulfates, fluoride, bacteria, pharmaceuticals, arsenic and much more.

Post Carbon / Block Carbon
Removes chlorine and organic chemicals that contribute to bad taste and odor.

AVAILABLE IN:
silver/black

Water Quality · LG · CE · RoHS · PL lead-free · ISO 9001 CERTIFIED · ETL